

### New $H^*(10)$ - Environmental Dosimeter

The Gamma-Sphere from Solid-State-Dosemetry-Laboratory of Research Center Karlsruhe, Institute of Radiology

#### Introduction

The environmental equivalent dose is intended to serve as a good approximation for an effective dose for a person who is positioned facing any direction within measuring range of the radiation field. In contrast to the old open-air-area-dose-measured-quantity  $H_x$  there is now the environmental-equivalent-dose  $H^*(10)$ , defined on a phantom at 10 mm depth in the ICRU-sphere (International Commission on Radiation Units and Measurement).



Therefore the previous  $H_x$ -photon-area-dosemeters are not or are only partly usable for measurement the new measured-quantity  $H^*(10)$ .  $H^*(10)$ -area-dosemeters should indicate the equivalent dose of penetrating radiation above 15 keV.

#### Materials and methods

Solid-State-Dosemetry-Laboratory use for measurement of photon radiation LiF: Mg, Ti (MTS-700) thermo luminescent detectors. TLD-700 without dosimeter-case shows  $H^*(10)$  incorrectly.

Figure 1 shows the results of irradiation of various materials. Al- and Cu-covers show too low responsivity of  $R_{H^*(10)}$  in the lower energy range, PE with PVC shows a good  $R_{H^*(10)}$ .





Figure 1:  $H^*(10)$  responsivity of TLD-700 in different materials with variable thickness.

PMMA with a thickness of 15 mm is quite suitable as a stand-alone material. The over-response compared to TLD without a filter (blue curve LiF: Mg, Ti in Figure 1) is significantly reduced. The resulting  $H^*(10)$ -response of TLD in a PMMA-sphere with 16 mm wall thickness is shown in Figure 2.





**Figure 2:** Energy responsivity of the  $H^*(10)$  gamma-sphere

The subdivision into a smaller spherical cap and larger spherical segment, with seal and thread, allows it to insert two MTS-700 chips in a 5 mm hole.

### Product Specification

Type of radiation:	Gamma- and X-rays
Measured-quantity:	Environmental-equivalent-dose $H^*(10)$
Material:	PMMA (polymethyl methacrylate)
Dimensions:	Ø35mm
Weight:	27g
Detector:	$^7\text{LiF:Mg;Ti}$ (MTS-700)
Measurement range:	0,05 mSv to 10 Sv
Nominal ranges:	Photon energy: 15 keV to 7 MeV Temperature: -10°C to 40°C Humidity: 10% to 90%
Variation coefficient of the dose results:	< 3%
Linearity deviation:	< 5%
Other types of radiation:	Neutron- and $\beta$ -rays insensitive
Exposure duration:	up to 1 year



All information in this brochure is subject to technical changes without notice.

**RadPro** International GmbH

*...Radiation Protection for the Radiation Professionals...*

Burger Straße 28  
42929 Wermelskirchen  
Germany  
Phone: +49 2196 889803  
Email: sales@radpoint.de  
Web: www.radpro-int.com

